


SR4210PCB

Board-Mount Receptacles



The SR4210PCB board-mount receptacle mates with all Datakey SlimLine™, Extended SlimLine, and RUGGEDrive™ memory tokens (see token datasheets for more details). The SR4210PCB receptacle features a right-angle, board-edge design with through-hole contacts.

All Datakey SlimLine receptacles feature “gold dome” contacts that perform reliably over a wear life of at least 50,000 insertion/removal cycles and employ a wiping mechanism to remove debris or build-up on the token’s contacts each time a token is inserted or removed. Also, SR4210PCB receptacles include a detent mechanism that contributes to token retention and gives users tactile and audible confirmation when an inserted token is fully engaged. The token/receptacle system provides a Last-On/First-Off (LOFO) contact that is used by system designers to detect when a memory token has been inserted or removed (contact ATEK Access Technologies for token detection details for RUGGEDrive memory tokens)². The SR4210PCB receptacle features flanges with 1/8-inch diameter non-threaded holes, which allows the receptacles to be secured to a PCB and/or panel with plastic rivets or other hardware.



MECHANICAL

Operating Life ⁴	50,000 Insertion/Removal Cycles Minimum
Insertion Force ⁴	400 gf Minimum / 2 kgf Maximum
Removal Force ⁴	300 gf Minimum / 2 kgf Maximum
Mass	~6 grams

ELECTRICAL

Contact Resistance	Beginning of Life: < 100 mΩ
	End of Life: < 500 mΩ

ENVIRONMENTAL

Storage Temperature	-40°C to +100°C
Operating Temperature	-40°C to +85°C
Relative Humidity	5% - 95% (non-condensing)
Altitude	MIL-STD-810H, Method 500.6, Proc. I & II ≤40,000 ft (12,192 m)
Mechanical Shock	MIL-STD-810H, Method 516.8, Proc. I
Vibration	MIL-STD-810H, Method 514.8, Proc. I

MATING COMPONENT(S)

Tokens	All SlimLine and RUGGEDrive Memory Tokens
--------	---

ORDERING INFORMATION¹

SR4210PCB	606-0050-100A
SR4210PCB ⁵	606-0050-105A

- 1: “A” suffix on part number indicates RoHS compliance. See CE declaration below for details.
- 2: Customers must design to meet Datakey interface specifications to provide for future memory device compatibility. Interface specifications available at datakey.com
- 3: RST signal used on IIT Series only.
- 4: Applications where a new token is used each time can reduce retention force prematurely.
- 5: Receptacles shipped in moisture bag (108/108 min/mult).

NOTES:

Conforms with Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011, and as amended by Directive 2015/863/EU, on the restriction of the use of certain hazardous substances in electrical and electronic equipment.




PINOUT CHART²

				RUGGEDRIVE™ LINE		
Pin #	Microwire	I ² C	SPI	DFX (SPI)	DFX (SD)	UFX (USB)
1	LOFO	LOFO	/Hold	Reserved	DAT1	NC
2	Power (V _{cc})	Power (V _{cc})	Power (V _{cc})	Data Out (DO)	DAT0	+5V
3	Chip Select (CS)	SIZE / RST ³	/Chip Select (/CS)	Ground (GND)	VSS	NC
4	Serial Clock (SK)	Serial Clock (SCL)	Serial Clock (SCK)	Serial Clock (SCLK)	CLK	DM
5	Data In (DI)	NC	Data In (SI)	Power (V _{cc})	VDD	DP
6	Data Out (DO)	Serial Add/Data (SDA)	Data Out (SO)	Data In (DI)	CMD	NC
7	Ground (GND)	Ground (GND)	Ground (GND)	/Chip Select (/CS)	DAT3	GND
8	LOFO	LOFO	LOFO	Reserved	DAT2	NC

NC = No Connection

SR4210PCB



Manufacturer's Recommendation: If using rivets to secure the receptacle, be sure to orient rivet such that the head of the rivet is in contact with the receptacle flange.

Drawing dimensions are in inches and millimeters [mm].
Dimensions are nominal and subject to manufacturer's tolerances.

221-0194-000 Rev. G 6/26

View our full product line at www.datakey.com

ATEK Access Technologies
210 10th Avenue NE
Brainerd, MN 56401 USA

Telephone:
1-800-523-6996
+1-218-829-9797

www.atekaccess.com

ATEK Access Technologies

Access the power of technology.